



MODERN LED LAMPS

CATALOG 2019



MODERN LED FLOOR LAMP

FLEXIBLE FRAME
CHARGER INCLUDED



REMOTE CONTROL
+ TOUCH SWITCH

3000K - 6500K



COLOR TEMPERATURE RANGE



PFLU19A

AC 100-240V 50/60Hz	CLASS II	5V/1A
35 000h	3000K 6500K COLOR TEMPERATURE	26 LED SMD (2835) LED QUANTITY
CLASS III	9W POWER	MAX 500lm
IP20 PROTECTION	120° ANGLE	<0,5s
<0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
-20°C +40°C TEMPERATURE RANGE	>80 Ra CRI	INCONVERTIBLE
0,1m MINIMAL DISTANCE		

PFLU19AB



PFLU19AW




LED FLOOR LAMP

2in1

READING LAMP: 5W 450LM
UPLIGHT: 18W 1620LM

STEEL + SATIN NICKLE PLATED
FOR THE TUBE AND BASE
GLASS SHADE



DIMENSIONS:
180cm



 AC 100-240V 50/60HZ	 CLASS II	 12V/1,5A
 25000h	 3000K COLOR TEMPERATURE	 46 LED SMD (XY-5730W3.J) LED QUANTITY
 CLASS III	 23W 18W (uplight) + 5W (reading) MAX POWER	 MAX 2070lm
 IP20 PROTECTION	 120° ANGLE	 ON OFF <0,5s
 60% <0,5s	 ON OFF x15000	 PF >0,5 POWER FACTOR
 0°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 -0,1m MINIMAL DISTANCE	 180° CABLE LENGTH 180CM	

BASE: 254X30MM
GLASS SHADE: 315X50MM

PFLF172S



FLOOR LAMP

- Ideal for many types of rooms
- Type of light bulbs: E14, E27
- Supply voltage: ~ 230-240 [V]

DIMENSIONS:

180cm

 CLASS II	IP20 PROTECTION
180cm CABLE LENGTH	25W 60W MAX

BULB TYPE

E14

BULB TYPE

E27



PFLF066GR

FLOOR LAMP

The PLATINET PFL lamp series features a high-quality, modern design with a stylish appearance that will give your interior a unique look.

The lamp fits perfectly into your living room, children's room, dining area, kitchen or office space. With its up-to-date design, it blends perfectly into both modern and classic interiors.

- Ideal for many types of rooms
- Uses E27 light bulbs - max 60W. E14 - max 25W.
- Supply voltage: 230-240V
- Construction: Metal
- Dimensions: 180 cm
- Length of the cable: 180cm
- Bulb not included

LAMPA PODŁOGOWA

Kolekcja lamp PLATINET PFL to designerska seria wykonana z najwyższej jakości materiałów. Odznacza się aktualnymi trendami na rynku z nowoczesnym i stylowym wyglądem. Lampa idealnie pasuje do: pokoju dziennego, młodzieżowego, salonu, jadalni, kuchni czy gabinetu, a dzięki swojemu designowi idealnie wtapia się w nowoczesne i klasyczne wnętrza.

- Idealna propozycja dla wielu rodzajów pomieszczeń
- Rodzaj żarówek: E27 max 60W. E14 - max 25W.
- Napięcie zasilania: 230-240V
- Materiał konstrukcji: Metal
- Wymiary: 180cm
- Długość przewodu: 180cm
- Brak żarówki w zestawie.



 **PLATINET**

BLOW LED LAMP

FLAME FLICKERING
BRIGHTNESS ADJUSTABLE
CHARGER INCLUDED

3000K



COLOR TEMPERATURE

 AC 100-240V 50/60HZ	 CLASS II	 5V/500mA
 35000h	3000K COLOR TEMPERATURE	3 LED SMD (2835) LED QUANTITY
 CLASS III	0,4W POWER	 MAX 30lm
IP20 PROTECTION	 120° ANGLE	 <0,5s
 60% <0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
 -0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 0-0,1m MINIMAL DISTANCE	 80 CABLE LENGTH 80CM	 LITHIUM BATTERY 3.7V/400MA



USB
UNIVERSAL SERIAL BUS



PDLZ2CGL



519075951446099


PLATINET



GLASS BASE LED DESK LAMP

DUAL POWER SOURCE


Ideal for study, reading, office
Special RGB glass base
Dimmable - 3 brightness levels
Colorful atmosphere lamp
Charger included
Sleek design



3 BRIGHTNESS LEVELS



TOUCH SWITCH



GLASS BASE



POSITION ADJUSTMENT



COLORED RGB GLASS



MICRO-USB PORT



4000K



COLOR TEMPERATURE

USB
UNIVERSAL SERIAL BUS

 AC 100-240V 50/60Hz	 CLASS II	 5V/1A
 35 000h	 4000K COLOR TEMPERATURE	 30 LED SMD (2835) LED QUANTITY
 CLASS III	 6W MAX POWER	 MAX 180lm
 IP20 PROTECTION	 120° ANGLE	 ON OFF <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 -20°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE	 EYE SAFE MODE	 CHARGER INCLUDED

PDLX14S



5 907595 446716

MODERN LED DESK LAMP

3-STEP MODE
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED

Size: 155x328x276mm
Weight: 393g



2800K-6800K



COLOR TEMPERATURE RANGE

 AC 100-240V 50/60Hz	 CLASS II	 5V/1A
 30 000h	 2800K 6800K COLOR TEMPERATURE	 40 LED SMD (2835) LED QUANTITY
 CLASS III	 3W POWER	 180lm
 IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	 ON OFF x80 000	 PF >0,5 POWER FACTOR
 0°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,4m MINIMAL DISTANCE		

PDLK6700W



5190759514439511

PDLK6700W

PLATINET

MODERN LED DESK LAMP

3-STEP MODE
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED

Size: 184x369x214mm
Weight: 353g



2800K-7000K



COLOR TEMPERATURE RANGE

 AC 100-240V 50/60Hz	 CLASS II	 5V/1A
 30 000h	2800K 7000K COLOR TEMPERATURE	40 LED SMD (2835) LED QUANTITY
 CLASS III	3W POWER	 180lm
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	ON OFF x80 000	PF >0,5 POWER FACTOR
 0°C +40°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 0,4m MINIMAL DISTANCE		

PDLK6703W



PDLK6703W

PLATINET

MODERN LED DESK LAMP

3-STEP MODE
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED

Size: 180x420x320mm
Weight: 660g



2800K-9000K



COLOR TEMPERATURE RANGE

 AC 100-240V 50/60HZ	 CLASS II	 12V/0.6A
 30 000h	 2800K 9000K COLOR TEMPERATURE	 60 LED SMD (2835) LED QUANTITY
 CLASS III	 6W POWER	 MAX 300lm
 IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	 ON OFF x80 000	 PF >0,5 POWER FACTOR
 0°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 ----- 0,4m MINIMAL DISTANCE		

PDLK065W



5190759514439371

PDLK065W

PLATINET

MODERN LED DESK LAMP

3-STEP MODE
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED



Size: 400x139x370mm
Weight: 1010g



Sleeping



Reading



60min



Natural



ALUMINUM FOLDING DESIGN



USB CHARGING



TOUCH CONTROL PANEL

2700K-5500K



COLOR TEMPERATURE RANGE

 AC 100-240V 50/60Hz	 CLASS II	 12V/1.5A
 30 000h	 2700K 5500K COLOR TEMPERATURE	 60 LED SMD (2835) LED QUANTITY
 CLASS III	 17W 7W (LED) + 10W (charger) MAX POWER	 MAX 270lm
 IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	 ON OFF x80 000	 PF >0,5 POWER FACTOR
 0°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 ----- 0,4m MINIMAL DISTANCE		

PDLKS091S



5190759514439441

PDLKS091S


PLATINET

MODERN LED DESK LAMP

3-STEP MODE
TOUCH CONTROL
FOLDABLE FRAME
CHARGER INCLUDED



FOLDING DESIGN



USB CHARGING



TOUCH CONTROL PANEL



ALUMINUM DESIGN



2800K-5700K



COLOR TEMPERATURE RANGE

AC 100-240V 50/60HZ	CLASS II	12V/1A
35000h	2800K 5700K COLOR TEMPERATURE	48 LED SMD (2835) LED QUANTITY
CLASS III	16,5W 10W (LED) + 6,5W (charger) MAX POWER	MAX 500lm
IP20 PROTECTION	120° ANGLE	ON <0,5s
60% <0,5s	ON OFF x15000	PF >0,5 POWER FACTOR
0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	INCONVERTIBLE
0,1m MINIMAL DISTANCE		

Size: 107x115x610mm Weight: 1.2kg



5 907595 439664

USB
UNIVERSAL SERIAL BUS

PDL509

PLATINET

BRUSH POT LED LAMP

FLEXIBLE FRAME
CHARGER INCLUDED



5500K
COLOR TEMPERATURE

 AC 100-240V 50/60HZ	 CLASS II	 5V/1A
 35000h	5500K COLOR TEMPERATURE	26 LED SMD [2835] LED QUANTITY
 CLASS III	6,5W POWER	 MAX 233lm
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
 -20°C +40°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 --- 0,1m  MINIMAL DISTANCE		

Size: 107x115x610mm Weight: 1.2kg



PDLJ5

 PLATINET

MODERN LED DESK LAMP

3-STEP DIMMER
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED



2in1

DESK & BEDSIDE TABLE
COLORFUL LIGHT LAMP

 AC 100-240V 50/60HZ	 CLASS II	 12V/1A
 35000h	5500K COLOR TEMPERATURE	45 LED SMD [2835] LED QUANTITY
 CLASS III	12W MAX POWER	 MAX 450lm
IP20 PROTECTION	 120° ANGLE	 <0,5s
 <0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
 -20°C +40°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 ----- 0,1m MINIMAL DISTANCE		

Size: 170x70x640mm Weight: 1.1kg



BUSINESS LED LAMP

LED DESK LAMP

Date & Time
Snooze Function
Temperature
Charger Included



5500K



COLOR TEMPERATURE



ALARM
CLOCK



 AC 100-240V 50/60HZ	 CLASS II	 12V/1A
 35 000h	 5500K COLOR TEMPERATURE	 36 LED SMD (2835) LED QUANTITY
 CLASS III	 10W MAX POWER	 MAX 450lm
 IP20 PROTECTION	 120° ANGLE	 ON OFF <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 0°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		

SIZE: 5103x125x653mm
WEIGHT: 1090g

PDLH1



BLUETOOTH SPEAKER LED LAMP



BLUETOOTH SPEAKER LED LAMP

FLEXIBLE FRAME
CHARGER INCLUDED
MODERN DESIGN



TOUCH CONTROL



5 907595 438902



COLOR TEMPERATURE

 AC 100-240V 50/60Hz	 CLASS II	 12V/1.5A
 35000h	 5500K COLOR TEMPERATURE	 36 LED SMD (4014) LED QUANTITY
 CLASS III	 12W 5W LED + 7W SPEAKER MAX POWER	 MAX 300lm
 IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 -20°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 MINIMAL DISTANCE 0,1m		

Size: 133x133x569mm Weight: 0.85kg

PDLM6

PLATINET

BLUETOOTH SPEAKER LED LAMP

FLEXIBLE FRAME
USB CHARGER



 AC 100-240V 50/60Hz	 CLASS II	 12V/1.5A
 35000h	5500K COLOR TEMPERATURE	36 LED SMD (4014) LED QUANTITY
 CLASS III	18W MAX POWER	 MAX 260lm
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
 0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		

Size: 133x133x505mm Weight: 0.85kg



USB
UNIVERSAL SERIAL BUS

PDLM6U

PLATINET

BLUETOOTH SPEAKER LED LAMP

FLEXIBLE FRAME
CHARGER INCLUDED
NIGHT LAMP FUNCTION
SPEAKERPHONE



 AC 100-240V 50/60HZ	 CLASS II	 12V/1.5A
 35000h	 5500K COLOR TEMPERATURE	 56 LED SMD (4014) LED QUANTITY
 CLASS III	 16W 8W LED + 8W SPEAKER MAX POWER	 MAX 300lm
 IP20 PROTECTION	 120° ANGLE	 ON OFF <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 -20°C +40°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 MINIMAL DISTANCE 0,1m		

Size: 133x133x569mm Weight: 0.85kg



5 907595 438834

PDLU5

PLATINET

BLUETOOTH SPEAKER LED LAMP

FLEXIBLE FRAME
USB CHARGER



5000K-6000K
COLOR TEMPERATURE RANGE

 AC 100-240V 50/60Hz	 CLASS II	 12V/1.5A
 35000h	5000K 6000K COLOR TEMPERATURE	24 LED SMD (4014) LED QUANTITY
 CLASS III	18W MAX POWER	 MAX 200lm
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	ON OFF x80 000	PF >0,5 POWER FACTOR
 0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 0,4m MINIMAL DISTANCE		

Weight: 810g Size: 130x140x410mm



5 907595 441230

USB
UNIVERSAL SERIAL BUS

PDLU9A

PLATINET

WIRELESS CHARGER LED LAMP



LED DIMMABLE DESK LAMP

WITH QI WIRELESS CHARGING PAD

Wireless charger for smartphone
5-grade brightness touch dimmer
3-Color temperature mode
Color changing night lamp
Touch sensitive control

 AC 100-240V 50/60HZ	 CLASS II	 12V/1.5A
 35 000h	2800K 5500K COLOR TEMPERATURE	45 LED SMD (2835) LED QUANTITY
 CLASS III	18W MAX POWER	 MAX 350lm
IP20 PROTECTION	 120° ANGLE	 <0,5s
 <0,5s	 ON OFF x15 000	PF >0,5 POWER FACTOR
 -20°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 ~0,1m MINIMAL DISTANCE	 EYE SAFE MODE	 CHARGER INCLUDED

PDLH10QBR



2800K-5500K
COLOR TEMPERATURE



WIRELESS
CHARGING 5V/1A



COLOR
NIGHT LIGHT PANEL

LEATHER-LIKE
TEXTURE



 **PLATINET**

WIRELESS CHARGER LED LAMP

FLEXIBLE FRAME



3000K-5500K
COLOR TEMPERATURE

 AC 100-240V 50/60Hz	 CLASS II	 12V/1.5A
 35000h	 3000K 4200K 5500K COLOR TEMPERATURE	 36 LED SMD (2835) LED QUANTITY
 CLASS III	 18W MAX POWER	 MAX 450
 IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 0°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		

Size: 188x66x420mm Weight: 0.95kg

WIRELESS CHARGER LED LAMP

COLORFUL NIGHT LIGHT



2700K-3300K



 AC 100-240V 50/60Hz	 CLASS II	 12V/1A
 35000h	2700K 3300K COLOR TEMPERATURE	24 LED SMD (5730) LED QUANTITY
 CLASS III	10W POWER	 <0,5s
IP20 PROTECTION	 180° ANGLE	PF >0,5 POWER FACTOR
 60% <0,5s	ON OFF x15 000	 INCONVERTIBLE
 -0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INDOOR
 --- 0,1m  MINIMAL DISTANCE		

Size: 207x52x86mm Weight: 500g



PDLU1


 **PLATINET**

AROMA DIFFUSER LED LAMP



AROMA DIFFUSER LED LAMP

COLORFUL LIGHTS
RGB OR MONOCHROMATIC



1500K-1900K

COLOR TEMPERATURE

 AC 100-240V 50/60Hz	 CLASS II	 24V / 0.65A
 35000h	1500K 1900K COLOR TEMPERATURE	96 LED SMD (3528) LED QUANTITY
 CLASS III	12W POWER	RGB COLORFUL LIGHTS
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <0,5s	ON OFF x15 000	PF >0,5 POWER FACTOR
 -0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 --- 0,1m  MINIMAL DISTANCE		


Size: 169x156mm Weight: 500g

AROMA DIFFUSER LED LAMP

COLORFUL LIGHTS
RGB OR MONOCHROMATIC



 AC 100-240V 50/60HZ	 CLASS II	 24V / 0.65A
 35000h	10W POWER	4 LED SMD (5050) LED QUANTITY
 CLASS III	 120° ANGLE	 <0,5s
IP20 PROTECTION	 ON OFF x15 000	PF >0,5 POWER FACTOR
 60% <0,5s	>80 Ra CRI	 INCONVERTIBLE
 °C -0°C +50°C TEMPERATURE RANGE	 DIMMER FUNCTION	 INDOOR
 ----- 0,1m MINIMAL DISTANCE		



Size: 169x156mm Weight: 500g

AROMA DIFFUSER LED LAMP

COLORFUL LIGHTS
RGB OR MONOCHROMATIC



 AC 100-240V 50/60Hz	 CLASS II	 24V / 0.65A
 35000h	 2,4MHz FREQUENCY	 9 LED SMD (3528) LED QUANTITY
 CLASS III	 13W POWER	 RGB COLORFUL LIGHTS
 IP20 PROTECTION	 120° ANGLE	 ON OFF <0,5s
 60% <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 -0°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		

Size: 168 x 211mm
Weight: 520g



MODERN USB LED DESK LAMP

POWER FROM USB CABLE
OPTIONAL: 4XAAA BATTERY
DIMMER CONTROL
TOUCH SWITCH

 LM SCALE
56, 106, 160 LM



5500K



 AC 100-240V 50/60HZ	 CLASS II	 5V/0,5A
 50 000h	5500K COLOR TEMPERATURE	18 LED SMD (2835) LED QUANTITY
 CLASS III	3,5W MAX POWER	 MAX 160lm
IP20 PROTECTION	 120° ANGLE	 <1s
 <1s	ON  OFF x100 000	PF >0,4 POWER FACTOR
 -10°C +45°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 --- 0,1m  MINIMAL DISTANCE		

PDL03BL

PDL03B



MODERN USB LED DESK LAMP

POWER FROM USB CABLE
OPTIONAL: 4XAAA BATTERY
DIMMER CONTROL
TOUCH SWITCH



LM SCALE
56, 106, 160 LM



5 907595 438261



5500K



COLOR TEMPERATURE RANGE

 AC 100-240V 50/60HZ	 CLASS II	 5V/0,5A
 50 000h	 5500K COLOR TEMPERATURE	 14 LED SMD (2835) LED QUANTITY
 CLASS III	 3,5W MAX POWER	 MAX 160lm
 IP20 PROTECTION	 120° ANGLE	 ON OFF <1s
 60% <1s	 ON OFF x100 000	 PF >0,4 POWER FACTOR
 -10°C +45°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 ----- 0,1m MINIMAL DISTANCE		



MODERN LED DESK LAMP

USB Port For Charging
Dimmer Control
Touch Switch



Technical Specifications

- 4200-6500K
- max: 300 lm
- Beam angle: 120°
- 5-step dimming and color tem
- Preature adjustment
- USB port for charging
- Touch countrol



PDL9

MODERN LED DESK LAMP

Calendar
Alarm Clock
Temperature



Technical Specifications

- 6W
- 2800-5500K
- max: 230lm
- Beam angle: 120°
- 5-step dimming and 3 options color temperature adjustment
- LCD display screen with calendar, alarm clock, temperature etc
- Touch control



PDL14

HOME OFFICE LAMPS



MODERN LED DESK LAMP

5-Step Dimmer
Touch Control
Foldable

Technical Specifications

- 6W
- 4000-4500K
- max: 240lm
- Beam angle: 50°
- 5-step dimming
- Touch control

2800-5500K



COLOR TEMPERATURE RANGE



PDL43



MODERN LED DESK LAMP

3-Step Dimmer
Touch Control
Foldable



Technical Specifications

- 6W
- 2800-5500K
- max: 210lm
- Beam angle: 120°
- 3 step dimming and 3 options color
- Temperature adjustment
- Touch control



PDL45

MODERN LED DESK LAMP

Modern design
Charger included
High quality

Technical Specifications

- 9W
- 3000K
- Max: 720 lm
- Beam Angle: 120°
- Aluminum
- On/Off Switch



3000K



COLOR TEMPERATURE RANGE

9W

MAX POWER



720LM



PDL518N

MODERN LED DESK LAMP

Modern design
Charger included
High quality

Technical Specifications

- 6W
- 3000K
- Max: 240 lm
- Beam Angle: 120°
- Aluminum
- On/Off Switch

3000K



COLOR TEMPERATURE RANGE

6W

POWER



MAX 480lm



PDL531

MODERN LED DESK LAMP

Modern design
Charger included
High quality



6W

POWER



MAX 480lm

Technical Specifications

- 6W
- 3000K
- Max: 240 lm
- Beam Angle: 120°
- Aluminum
- On/Off Switch



PDL531N

MODERN LED DESK LAMP

Modern design
On/Off Switch
Long cable

Technical Specifications

- Max Power: 9W
- 3000K
- Max: 720 lm
- Beam Angle: 120°
- Aluminum
- On/Off Switch



**MODERN
DESIGN**

ALUMINIUM
+
PC

9W

MAX POWER

105

LED SMD
(3014)

LED QUANTITY




PDL578

MODERN LED DESK LAMP

Modern design
On/Off Switch
Long cable

Technical Specifications

- Max Power: 3W
- 3000K
- Max: 240 lm
- Beam Angle: 120°
- Aluminum
- On/Off Switch



**MODERN
DESIGN**

ALUMINIUM
+
PC

3W

MAX POWER

33

LED SMD
(3014)

LED QUANTITY



PDL538

MODERN LED DESK LAMP

Touch switch
Dimmer control
Flexible lamp
Charger included
Compartment for batteries

Technical Specifications

- 3,5W
- 5500K
- Max: 160 lm
- Beam Angle: 110°
- 3-step Dimming
- Touch Countrol
- Charger Included
- Compratmt for batteries: 4xAAA (not included)



MODERN LED DESK LAMP

Touch switch
Dimmer control
Clip desk holder
Flexible lamp
Charger included



Technical Specifications

- 3,5W
- 5500K
- Max: 160 lm
- Beam Angle: 110°
- 3-step Dimming
- Touch Control
- Clip Desk Holder
- Charger Included



PDL01C

BLUETOOTH LED LAMP SPEAKER

Compact Speaker
6 Led Light Colors
Controlled by Touch
Built-in Battery
Disco Mode

2in1
led lamp + speaker



Technical Specifications • controlled by a touch • 6 colours: white (day light), red, purple, green, pink, blue • 3 brightness of led day light • Lock/Unlock button for led light • Built in TF card slot • Built in microphone • 3.5mm AUX for non-Bluetooth devices • Supported Bluetooth profiles HSP, HFP, A2DP and AVRCP • Bluetooth operating distance 10 meters (equal to 33 feet) • Speaker output power 5W • Distortion ≤1% • Microphone sensitivity -40db • Built-in lithium battery 1200mAh • Playback time 2 h • Charging via port microUSB • Charging time: 3 h

30lm RGB LIGHT 50lm NATURE LIGHT LUMINOUS	 360° ANGLE	 AC DC 5V	 1A
ON  OFF x20 000	3000K COLOR TEMPERATURE	8 RGB LIGHT (8x 5050) 8 NATURE LIGHT (8x 2835) LED QUANTITY	0,3W RGB LIGHT 0,5W NATURE LIGHT MAX LED POWER




PDLSB01

MODERN LED DESK LAMP

Touch Switch
Dimmer Control
Charger Included
Compartment For Batteries

Warm Yellow Backlight Function



Technical Specifications

- Max Power: 4,5W
- 5500K
- Max: 160 lm
- Beam Angle: 110°
- 3-step Dimming
- Touch Control
- Charger Included
- Compartment for batteries: 4xAAA (not included)

PDL02B black



5 907595 436014

PDL02W white



5 907595 436021

5500K



COLOR TEMPERATURE RANGE

**FLEXIBLE
LAMP**

COMPARTMENT
FOR BATTERIES



COLOR LIGHTS LAMPS





MODERN LED DESK LAMP

3-STEP DIMMER
TOUCH CONTROL
FLEXIBLE FRAME
CHARGER INCLUDED


3-STOPNIOWY ŚCIEMNIACZ
STEROWANIE DOTYKOWE
ELASTYCZNE RAMIE
WBUDOWANA ŁADOWARKA



2in1

DESK & BEDSIDE TABLE
COLORFUL
LIGHT LAMP

 AC 100-240V 50/60HZ	 CLASS II	 5V/1.5A
 35000h	5500K COLOR TEMPERATURE	34 LED SMD (3528) LED QUANTITY
 CLASS III	7W MAX POWER	 MAX 260lm
IP20 PROTECTION	 120° ANGLE	 ON <0,5s
 60% <1s	 ON OFF x15 000	PF >0,4 POWER FACTOR
 -20°C +40°C TEMPERATURE RANGE	>80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		



LM SCALE
28, 108, 260 LM

PDL20

PDL20B

PDL20BL


PDL20P





MODERN LED DESK LAMP

3-STEP DIMMER
FLEXIBLE ARM
ADAPTER INCLUDED



 AC 220-240V 50/60Hz	 CLASS II	 5V/1A
 35000h	 5500K COLOR TEMPERATURE	 16 LED SMD (2835) LED QUANTITY
 CLASS III	 5W MAX POWER	 MAX 200lm
 IP20 PROTECTION	 120° ANGLE	 ON/OFF <0,5s
 60% <0,5s	 ON/OFF x15 000	 PF >0,5 POWER FACTOR
 -0°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		

2in1

DESK & BEDSIDE TABLE
COLORFUL LIGHT LAMP

PDLQ11



5 907595 437660



MODERN LED DESK LAMP

5-Step Dimmer
Touch Control
Flexible Frame
Charger Included

5500K



COLOR TEMPERATURE

Technical Specifications

- Max Power: 9,5W
- 5500K
- Max: 450 lm
- Beam Angle: 110°
- 5-step Dimming
- Touch Control
- Charger Included

2in1

DESK & BEDSIDE TABLE
COLORFUL LIGHT LAMP



PDLT5



MODERN LED DESK LAMP

3-Step Dimmer
Touch Control
Flexible Frame
Charger Included

5500K



COLOR TEMPERATURE

Technical Specifications

- Max Power: 7W
- 5500K
- Max: 230 lm
- Beam Angle: 120°
- 5-step Dimming
- Touch Control
- Charger Included

2in1

DESK & BEDSIDE TABLE
COLORFUL LIGHT LAMP



PDLQ8



MODERN LED DESK LAMP

3-Step Dimmer
Touch Control
Flexible Frame
Charger Included

5500K



COLOR TEMPERATURE

Technical Specifications

- Max Power: 6W
- 5500K
- Max: 200 lm
- Beam Angle: 120°
- 3-step Dimming
- Touch Control
- Charger Included




2in1

DESK & BEDSIDE TABLE
COLORFUL LIGHT LAMP



PDLQ10

**CLOCK
CALENDAR
ALARM
LED LAMP**





BRUSH POT LED LAMP

Date & Time
Snooze Function
Temperature
Charger Included

5500K



COLOR TEMPERATURE

Technical Specifications

- Max Power: 7W
- 5500K
- Max: 230 lm
- Beam Angle: 120°
- 3-step Dimming
- Touch Countrol
- Charger Included



7W

MAX POWER



MAX 230lm

5500K

COLOR
TEMPERATURE



PDLU6



BUSINESS LED LAMP

LED DESK LAMP

Date & Time
Snooze Function
Temperature
USB Charger



SIZE: 140x183x605mm
WEIGHT: 840g

 LEATHER
STRUCTURE

 CHARGING
PORT



3000K-6000K



COLOR TEMPERATURE

 AC 100-240V 50/60HZ	 CLASS II	 12V/1A
 35 000h	 3000K 6000K COLOR TEMPERATURE	 36 LED SMD (2835) LED QUANTITY
 CLASS III	 14W 8,5W (LED) + 5,5W (charger) MAX POWER	 MAX 350lm
 IP20 PROTECTION	 120° ANGLE	 <0,5s
 <0,5s	 ON OFF x15 000	 PF >0,5 POWER FACTOR
 -20°C +50°C TEMPERATURE RANGE	 >80 Ra CRI	 INCONVERTIBLE
 0,1m MINIMAL DISTANCE		
 LM SCALE 12, 71, 207, 270, 350 LM		

PDLU13



5 907595 438209

BUSINESS LED LAMP

Date & Time
Snooze Function
Temperature
Charger Included



Technical Specifications

- Max Power: 7W
- 5500K
- Max: 200 lm
- Beam Angle: 120°
- Touch Control
- Charger Included

FAUX LATHER
PATTERN DESIGN



PDU2BR



MODERN LED DESK LAMP

Temperature
Alarm Clock
Calendar
Charger included

3000-6000K



COLOR TEMPERATURE RANGE

Technical Specifications

- Max Power: 12W
- Max: 500 lm
- Beam Angle: 120°
- 5-step Dimming and Color Temperature Adjustment
- LCD Display Screen
- Touch Control



PDLM3S

LED STRIP WITH MOTION SENSOR

- Shut OFF Timer
- Adjustable Detecting Range

TIME DELAY: min. 3s, max. 60s

DETECTING RANGE: min. 1m, max. 5m

LIGHT SENSITIVITY: min: Bright, max: Dark

PL TAŚMA LED Z CZUJNIKIEM RUCHU

Czujnik ruchu – Gdy osoba znajdzie się w zasięgu, światło będzie działać.


Gdy osoba opuści pomieszczenie lub położy się na łóżku po kilku sekundach światło zostanie automatycznie wyłączone.

Czas świecenia, zasięg wykrywania oraz czułość czujnika można regulować.



STRIP LENGTH

1,5m





MOTION SENSOR

WHERE YOU GO, LIGHT ON!


This unique nightlight provides a soft, warm light at night when you step out of bed.

As your foot touches the floor, the room is softly illuminated to guide you gently and safely through the room. No disturbing glare to wake others. No fumbling to find the light switch in the dark.



AC 220-240V 50/60Hz	CLASS II	12V/0.5A
30000h LIFETIME	3000K COLOR TEMPERATURE	45 LED SMD (3528) LED QUANTITY
CLASS III	3.6W POWER	255lm LUMEN
IP44 PROTECTION	120° ANGLE	ON/OFF TIME
60% DIMMING	ON/OFF TIME	PF >0.5 POWER FACTOR
-0°C ~ +50°C TEMPERATURE RANGE	>80 Ra CRI	INCONVERTIBLE
--- 0,1m MINIMAL DISTANCE		

MOTION SENSOR



WHERE YOU GO, LIGHT ON!

Automatic Sensor

When people approach the detecting area, the light will be on. When people leave or lie on the bed after several seconds, the light will be off automatically.

The time delay, detecting range and the light sensitivity can be adjusted.

PLSB15

PLATINET

LED STRIP WITH MOTION SENSORS

- Shut OFF Timer
- Adjustable Detecting Range

TIME DELAY: min. 3s, max. 60s

DETECTING RANGE: min. 1m, max. 5m

LIGHT SENSITIVITY: min: Bright, max: Dark

PL TAŚMA LED Z CZUJNIKIEM RUCHU

Czujnik ruchu – Gdy osoba znajdzie się w zasięgu, światło będzie działać.

Gdy osoba opuści pomieszczenie lub położy się na łóżku po kilku sekundach światło zostanie automatycznie wyłączone.

Czas świecenia, zasięg wykrywania oraz czułość czujnika można regulować.



STRIP LENGTH



3m
(1,5m x 2)



2X MOTION SENSOR


WHERE YOU GO, LIGHT ON!

This unique nightlight provides a soft, warm light at night when you step out of bed. As your foot touches the floor, the room is softly illuminated to guide you gently and safely through the room. No disturbing glare to wake others. No fumbling to find the light switch in the dark.



AC 220-240V 50/60Hz	CLASS II	12V/0.5A
3000h LIFE TIME	3000K COLOR TEMPERATURE	90 LED SMD (3528) LED QUANTITY
CLASS III	7.2W POWER	450lm LUMEN
IP44 PROTECTION	120° ANGLE	ON/OFF TIME
60% DIMMING	ON/OFF TIME	PF >0.5 POWER FACTOR
-0°C +50°C TEMPERATURE RANGE	>80 Ra CRI	INCONVERTIBLE
MINIMAL DISTANCE 0,1m		

MOTION SENSORS



WHERE YOU GO, LIGHT ON!

Automatic Sensor

When people approach the detecting area, the light will be on. When people leave or lie on the bed after several seconds, the light will be off automatically. The time delay, detecting range and the light sensitivity can be adjusted.



Distributor:

PLATINET S.A.

Sliwiaka 48 St.,
30-798 Krakow, PL

tel. +48 12 65 10 580
export@platinet.eu

www.platinet.eu